




## Bearing equipment manufacturing Co., Ltd



### INA NX10 complex bearings

Bearing No. NX10

Size	10x19x18 mm
Bore Diameter	10 mm
Outer Diameter	19 mm
Width	18 mm
$F_w$	10 mm
D	19 mm
C - 18 mm / Tolerance: -0,25	18 mm / Tolerance: 0,25
$C_1$	4,7 mm
$C_2$	10 mm
$D_1$	21,9 mm
$d_a$	14,6 mm
$d_w$	10 mm / Tolerance: E8
$r_{a \max}$	0,3 mm
$r_{\min}$	0,3 mm
m	25 g / Weight
$C_r$	5000 N / Dynamic load rating (radial)
$C_{0r}$	3700 N / Static load rating (radial)
$C_a$	4600 N / Dynamic load rating (axial)
$C_{0a}$	7200 N / Static load rating (axial)
$C_{ur}$	720 N / Fatigue limit load, radial
$C_{ua}$	320 N / Fatigue limit load,

NX10 Bearing 2D drawings and 3D CAD models



## Bearing equipment manufacturing Co., Ltd

	axial
$n_G$	11000 1/min / Limiting speed
- IR6X10X10-IS1 / Suitable inner ring	IR6X10X10IS1 / Suitable inner ring
Category	Thrust Roller Bearing
Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.031
EAN	4047643203470
Product Group	B00234
Rolling Element	Combination - Needle Roller and Thrust Ball Bearing
Self Aligning	No
Component Description	Roller Assembly plus Raceways
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	Yes
Cage Material	Steel
Precision Class	ABEC 1   ISO P0
Long Description	10MM Bore 1; 10MM Bore 2; 19MM Outside Diameter; 18MM Height; Combination - Needle Roller and Thrust Ball Bearing; Single Direction; Not Self Aligning; Banded; Steel Cage; ABEC 1   ISO P0; Roller Asse
Inch - Metric	Metric
Category	Thrust Roller Bearings
UNSPSC	31171537
Harmonized Tariff Code	8482.80.00.40



## Bearing equipment manufacturing Co., Ltd

Noun	Bearing
Keyword String	Combination
Manufacturer URL	<a href="http://www.ina.com">http://www.ina.com</a>
Manufacturer Item Number	NX10
Weight / LBS	0.055
Bore 1	0.394 Inch   10 Millimeter
Bore 2	0.394 Inch   10 Millimeter
Outside Diameter	0.748 Inch   19 Millimeter
Height	0.709 Inch   18 Millimeter
Overall Height with Aligning Washer	0 Inch   0 Millimeter